




E-6 電磁溢流閥

Solenoid Control Relief Valves

BST, BSG, SBSG, BHSB, BHST系列



選購指南 HOW TO ORDER

BS	G	-06	H	-2B2	-A2	5	-D5	-2P
系列編號 SERIES NUMBER	接續型式 TYPE OF CONNECTION	通徑 VALVE SIZE	壓力調整範圍 PRESSURE ADJ. RANGE (Kgf/cm ²)	功能型式如下表 TYPE OF FUNCTIONS FOR OPTIONAL VENTING CONDITIONS AS BELOW	線圈型式 SOLENOID TYPE	頻率 HZ	接線盒型式 TERMINAL	多段壓力控制 MULTIPRESSURE CONTROL
BS BHS SBS	G: SUB-PLATE TYPE T: THREADED TYPE	06 10	B: 10-70 C: 35-140 H: 70-250		A1: AC110V D1: DC12V A2: AC220V D2: DC24V A3: AC380V	5: 50HZ 6: 60HZ	D4: 接線盒 D5: JIS D5: 插頭 D5: DIN	-單段壓力控制 NONE SINGLE PRESSURE CONTROL 2P: 兩段壓力控制 DUOPRESSURE CONTROL 3P: 三段壓力控制 TRIPLE PRESSURE CONTROL

注：本系列電液換向閥，必須與電磁閥配合使用，電磁閥規格如下表，但訂購時，祇計本體，電磁閥價格另計。
Remark: the series valve must be used together with solenoid valve, the model of solenoid valves as below, the price we offer is body only, the solenoid valve with another price.


油壓記號及控制型式 GRAPHICAL SYMBOL & VENT MODEL

型號 MODEL	多段壓力控制 MULTI-PRESSURE CONTROL	油壓記號 GRAPHICAL SYMBOL	線圈激磁與導壓動作狀態 FUNCTIONS OF COIL & VENTINGS		導壓出孔動作狀態 OPTIONAL VENTING CONDITIONS
			線圈A COIL A	線圈B COIL B	
2B2	單段壓力控制 SINGLE PRESSURE CONTROL		—	OFF ON	油槽(卸載) TANK(UNLOADING) B孔 B PORT
2B5A	單段壓力控制 SINGLE PRESSURE CONTROL		—	—	閉狀態(調壓閥設定) PRESSURE FOLLOWING RELIEF 油槽(卸載) TANK(UNLOADING)
2B2	2P: 兩段壓力控制 DUOPRESSURE CONTROL		—	OFF ON	A孔 A PORT B孔 B PORT
3C2	3P: 三段壓力控制 TRIPLE PRESSURE CONTROL		OFF ON	OFF OFF	閉狀態(調壓閥設定) PRESSURE FOLLOWING RELIEF B孔 B PORT
3C3	2P: 兩段壓力控制 DUOPRESSURE CONTROL		OFF ON	OFF ON	油槽(卸載) TANK(UNLOADING) A孔 A PORT B孔 B PORT

E-6 二段壓力、三段壓力 電磁溢流閥

Solenoid Control Relief Valves

BSG-2P, BSG-3P, BST-2P, BST-3P系列



性能表 SPECIFICATION

型號 MODEL		最高使用壓力 MAX. OPERATING PRESSURE Kgf/cm ²	壓力調整範圍 PRESSURE ADJ. RANGE Kgf/cm ²	最大流量 MAX. FLOW (l/min)	重量 WEIGHT (KG)	
板式 SUB-PLATE TYPE	管式 THREAD TYPE				板式 SUB-PLATE	管式 THREAD TYPE
BSG-03	BST-03	250	B:7-70 C:35-140 H:70-250	100	7.1	6.5
BSG-06	BST-06			200	8.0	7.4
BSG-10	BST-10			400	11.3	11.1
BSG-03-2P	-			100	10.0	-
BSG-03-3P	-			100	10.0	-
BSG-06-2P	BST-06-2P			200	11.0	9.0
BSG-06-3P	BST-06-3P			200	11.0	9.0
SBSG-03	-			100	6.3	-
SBSG-06	-			200	7.2	-
SBSG-03-2P	-			100	10.8	-
SBSG-06-2P	-			200	11.7	-

E-7 減壓閥

Reducing Valves

RT, RCT, RG, RCG系列



選購指南 HOW TO ORDER

RC	G	-03	B
系列編號 SERIES NUMBER R: REDUCING VALVE RC: REDUCING VALVE(WITH CHECK VALVE)	接續型式 TYPE OF CONNECTION G: SUB-PLATE TYPE T: THREADED TYPE	通徑 VALVE SIZE 03 06 10	壓力調整範圍 PRESSURE ADJ. RANGE B: 5-70 Kgf/cm ² C: 35-140 Kgf/cm ² H: 70-250 Kgf/cm ²

性能表 SPECIFICATION

型號 MODEL		最高使用壓力 MAX. OPERATING PRESSURE Kgf/cm ²	壓力調整範圍 PRESSURE ADJ. RANGE Kgf/cm ²	額定流量 RATED FLOW (l/min)	泄油量 DRAIN (l/min)	重量 WEIGHT(KG)	
板式 SUB-PLATE TYPE	管式 THREAD TYPE					板式 SUB-PLATE	管式 THREAD TYPE
RG-03 RCG-03	RT-03 RCT-03	250	B:5-70 C:35-140 H:70-250	50	0.8	4.5 5.4	4.3 4.8
RG-06 RCG-06	RT-06 RCT-06			125	1.0	6.8 8.1	6.9 7.8
RG-10 RCG-10	RT-10 RCT-10			250	1.2	11.0 13.8	12.0 13.8